

**Trusted Partners In Construction Chemicals** 



# MCON WALL PUTTY

WHITE CEMENT BASED WATERPROOF WALL PUTTY

## **Product Description:-**

MCON WALL PUTTY is a white cement based, water resistant wall putty, which requires precise quantity of water to make a creamy paste as an inert material for substrate. This is especially used to seal the pinholes and the blow holes getting exposed on concrete / plastered surfaces and to provide smooth even surface for next coating. It can be applied on internal as well as external surfaces. It gives better adhesion and increases the life of paints.







**Trusted Partners In Construction Chemicals** 

## **Areas of Application:-**

- Use on both precast and concrete structures like sand cement plaster, level brick work and block work, exposed concrete.
- ✓ Plywood.
- AC sheets.
- Gypsum boards.
- Can also be applied for redecoration on firm, old painted areas.

#### Features & Benefits :-

- Synthetically bound ready to use compound for inert filler material.
- Only precise quantity of water to be added.
- Ensures use on all common types of building interiors.
- Excellent adhesion & thixotropicness.
- Due to good bonding property it is more durable and no chalking.
- Excellent finishing and easy to apply.
- Completely applied putty will not allow water penetration.
- Provides smooth, silky and featheredged finish to substrate to facilitate better texture of paint.
- ✓ Application of MCON WALL PUTTY with workmanship makes exterior and interior look aesthetic. No curing is required.
- Prevents growth of algae and fungi on walls.
- It is in dry powder form and does not produce any kind of filth smell at the time of application.



**Trusted Partners In Construction Chemicals** 

# **Methods of Application:**

#### **Surface Preparation:**

Use on both precast and concrete structures like sand cement plaster, level brick work and block work, exposed concrete.

There should be a time gap of atleast 10 days before MCON WALL PUTTY application is done on newly plastered surfaces.

Ensure that the surface is fairly even.

If concrete surfaces is to be painted, it shall be washed with a water jet at 3000 psi and all loose concrete should be removed. All pin holes and blow holes should get opened.

#### Mixing:

MCON WALL PUTTY is a ready to use material.

Take 2.5 to 3 parts of powder to 1 part of water by volume and mix it thoroughly for 10-15 mins.

### **Coating Application:**

Apply the prepared material with putty knife from bottom to top by ensuring complete filling of holes with putty material and featheredged finish.

The coating should be about 1 mm thick.

Second coat of MCON WALL PUTTY depends up on the exposed surface after first coat (generally both coat do not exceed 2 mm) and leave the surface to dry overnight.



**Trusted Partners In Construction Chemicals** 

### Finishing:

Make sure that the material has fully covered the substrate and dried. If putty applied surface is rough, surface should be made smooth by rubbing suitable emery paper on it. Ensure that the paper is fine and does not cause scratches on the MCON WALL PUTTY coating area.

The MCON WALL PUTTY area is now ready for painting.

### **Painting:**

The smooth surface finished with MCON WALL PUTTY does not require any putty or primer before paint application. Just apply any paint as per the manufacturer's standard specification. In fact painting can commence within a few hours of MCON WALL PUTTY.



#### **Coverage:-**

2.5 to 3 m<sup>2</sup> per kg when applied at a thickness of 1 mm - Single Coat.





**Trusted Partners In Construction Chemicals** 

## **Shelf Life & Storage:-**

6 months in original packing if stored at room temperature i.e.25° C



## Packing:-

1 kg., 5 kg., 20 kg., & 40 kg.plastic lined sacks.



\*(Mcon Rasayan has maintained the highest level of Quality and Consistency by following Systems is certified and as an ISO 9001: 2015, ISO 14001:2015 & ISO 18001:2015 Company.)

Address: Gala No.6, Bardanwala Estate, Bandivali Hill Road, Jogeswari (W), Mumbai - 400102

Call us: +91 8657448832 / 022- 26790031

Email id: salesmcon16@gmail.com

Website: www.mconrasayan.com/www.mconrasayan.net

Follow us on:





