



MCON CRACK FILLER PASTE

READY TO USE ACRYLIC CRACK FILLING PASTE WITH IMPROVED BONDING & WATERPROOFING CHARACTERISTICS FOR FILLING INTERNAL & EXTERNAL CRACKS IN PLASTER



Product Description :-

MCON CRACK FILLER PASTE is an acrylic polymer based white crack filler made of acrylic emulsion polymer, properly selected graded fillers & additives. It provides a strong bond with flexibility which accommodates the cracks in the plaster and provides a water resistant surface with aesthetic appearance.

Features & Benefits :-

- Paint ability - Over coat-able by any type of polymer based paints, after 24 hours.
- Flexibility - Flexible, therefore does not crack & accommodates minor movements in cracks.
- Application advantage - Can be applied on damp surfaces but not on cracks with running water.
- Paint ability - Over coat-able by any type of polymer based paints, after 24 hours.
- Ease of application – Easy to apply by putty knife similar to conventional putties.

Areas of Application :-



Horizontal & Vertical cracks



Internal Crack



External Crack



Hair Line Cracks

Technical Specification :-

Colour	Milky White
Form	Paste
Sp. Gravity	1.50
Consistency	Viscous Paste Type
Water Resistance	Excellent





MCON CRACK FILLER PASTE

READY TO USE ACRYLIC CRACK FILLING PASTE WITH IMPROVED BONDING & WATERPROOFING CHARACTERISTICS FOR FILLING INTERNAL & EXTERNAL CRACKS IN PLASTER



Easy To Apply :-

- Surface preparation is vital for effective adhesion and bonding of MCON CRACK FILLER PASTE.
- To start with, free the surface from laitance, loose dust particles, oil, grease and other dirt.
- Press MCON CRACK FILLER PASTE firmly into the crack with a spatula or putty knives and level with the surface.
- Care must be taken to avoid formation of cavities or bubbles during application.
- Allow it set for 24 hours and then apply another coat of MCON CRACK FILLER PASTE.
- Further POP or painter's putty application can be taken up once it is fully dry. For best results allow MCON CRACK FILLER PASTE to cure for 7 days.



Coverage :-

40 - 45 Rft Per Kg /
5 mm Cracks



Packing :-

1 & 5 Kgs

Shelf Life :-

- Store away from direct sunlight. 12 months from date of manufacture

Safety & Precautions :-

- MCON CRACK FILLER PASTE is non-toxic, non-flammable and nonhazardous. However, any splashes on any part of the human body must be washed with plenty of water.

An ISO 9001 : 2015 - An ISO 14001 : 2015 - AN BS OHSAS 45001 : 2018

MCON RASAYAN PVT. LTD.

Trusted Partner In Construction Chemicals

Corporate Office : Gala No. 6 , Bardanwala Estate , Bandivali Hill Road , Jogeshwari (W) , Mumbai - 400 102 , Maharashtra , India .

Consumer Care : 022 - 26790031 • Email Id : info@mconrasayan.com • Visit us : www.mconrasayan.com • Follow Us :   