



## MCON READY PLASTER RENDER

### CEMENT SAND THIN SECTION RENDER



#### Product Description :-

MCON READY PLASTER RENDER is a cement sand fiber reinforced, ready to use render for internal & external surface corrections purpose. It is convenient, easy to use, strong and binds better to its substrate. This product is composed of good quality cement, properly selected aggregates, Fibres & additives. Its well graded aggregates which are clean and silt free ensure that the plaster has a very cohesive and smooth finish. The waterproofing and bonding polymers give the plaster a better bonding with water tight characteristics. MCON READY PLASTER RENDER is easy to use as it can be applied with trowel.

#### Features & Benefits :-

- Crack free & firm surface that preserves beauty of building for longer time.
- Moisture resistant - Offers excellent resistance to moisture ingress.
- Sufficiently flexible to accommodate thermal & physical movements.
- Better bond than conventional cement based mortar.

#### Areas of Application :-



*Brick & Block Work*



*Concrete Substrates*




*Internal Plastering*



*External Plastering*

#### Technical Specification :-

Binder	Grey Portland Cement 53 Grade
Dry Density	1.6 kg/ltr
Wet Density	1.9 kg/ltr (mixed with water)
Water Intake	150 – 200 ml per kg (approx 6 - 8 Ltr in a bag of 40 kg)
POT Life	75 Minutes
Thickness	5 - 6 mm per single coat





## MCON READY PLASTER RENDER

CEMENT SAND THIN SECTION RENDER



### Easy To Apply :-

- Clean the substrate , free from all loose particle, oil & grease, paints or free sand.
- Water jet cleaning is advisable.
- Wet the surface before application of the plaster.
- Mix one bag of 40 kg of MCON READY PLASTER RENDER with 6.5 -7 ltr of water using a mechanical mixer.
- Small quantity can be mixed using a trowels and a bucket. All care should be taken that the mixing is done thoroughly.
- Use the mixture within 1 ¼ hrs (75 min) after addition of water.
- Curing of the plastered surface can be done after 10 – 12 hrs and should be done for 2 – 3 days.



### Coverage :-

*50 - 60 sq. ft per 40 kg bag at 5 - 6 mm thickness.*



### Packing :-

*40 Kgs*

### Shelf Life :-

- 6 months from manufacture in original unopened bags if stored in dry conditions.

### Safety & Precautions :-

- Care should be taken to avoid contact with eyes, skin, mouth and food stuff. Any splashes on the human body must be washed with plenty of water.

An ISO 9001 : 2015 - An ISO 14001 : 2015 - AN BS OHSAS 45001 : 2018

**MCON RASAYAN PVT. LTD.**

Trusted Partner In Construction Chemicals

Corporate Office : Gala No. 6 , Bardanwala Estate , Bandivali Hill Road , Jogeshwari (W) , Mumbai - 400 102 , Maharashtra , India .

Consumer Care : 022 - 26790031 • Email Id : [info@mconrasayan.com](mailto:info@mconrasayan.com) • Visit us : [www.mconrasayan.com](http://www.mconrasayan.com) • Follow Us :   